

Cable Shears

95

Short design, length only 20" (500 mm)
Lightweight, high leverage

- > for cutting copper and aluminum cables, single and multi-stranded wire
- > not suitable for steel wire and wire ropes
- > precision ground, hardened blades
- > clean and smooth cut without crushing and deformation
- > less effort required due to favorable lever ratio and special blade geometry
- > pinch guard prevents operators' fingers being pinched
- > adjustable bolted joint
- > cutter head: vanadium electric steel, forged, oil-hardened
- > handle shank: aluminum tube, high-strength



Large cutting capacity: max. 1 1/16"
(27 mm) dia. / 150 mm²



95 12 500
⚡ ⚠



95 17 500
⚡ 1000 V ⚠ ⚡ ⚠

Product Number	Packaging	↔ Inch mm	⚡ ⚠	Head	Handles	Cutting capacities		AWG	⚖ lbs
						⚡ Ø Inch Ø mm	⚡ mm ²		
95 12 500		20 500	⚡ ⚠	polished	multi-component grips	1 1/16 27	150	5/0	2.49
95 17 500		20 500	⚡ 1000 V ⚠ ⚡ ⚠	polished	plastic dipped insulated, VDE-tested	1 1/16 27	150	5/0	3.26

Cable Shears

95

- > for cutting copper and aluminum cables, single and multi-stranded wire
- > not suitable for steel wire and wire ropes
- > precision ground, hardened blades
- > clean and smooth cut without crushing and deformation
- > favorable lever ratio due to toggle lever
- > pinch guard prevents operators' fingers being pinched
- > adjustable bolted joint
- > bolted cutter head, replaceable
- > blade head: high-grade chrome vanadium electric steel, forged, oil-hardened
- > handle: steel tube



95 27 600
⚡ 1000 V ⚠ ⚡ ⚠

Product Number	Packaging	↔ Inch mm	⚡ ⚠	Head	Handles	Cutting capacities		AWG	⚖ lbs
						⚡ Ø Inch Ø mm	⚡ mm ²		
95 27 600		23 1/2 600	⚡ 1000 V ⚠ ⚡ ⚠	polished	plastic dipped insulated, VDE-tested	1 1/16 27	150	5/0	5.08
95 29 600	Spare cutter head for 95 27 600								